N-Channel 30-V (D-S) MOSFET


Key Features:
- Low $r_{DS(on)}$ trench technology
- Low thermal impedance
- Fast switching speed


Typical Applications:
- DC/DC Conversion
- Power Routing
- Motor Drives

PRODUCT SUMMARY		
V_{DS} (V)	$r_{DS(on)}$ (mΩ)	I_D (A)
30	5.5 @ V_{GS} = 10V	21
	7.8 @ V_{GS} = 4.5V	17

Pb-free
RoHS COMPLIANT
HALOGEN FREE

DFN3x3-8L





ABSOLUTE MAXIMUM RATINGS (T_A = 25°C UNLESS OTHERWISE NOTED)				
Parameter		**Symbol**	**Limit**	**Units**
Drain-Source Voltage		V_{DS}	30	V
Gate-Source Voltage		V_{GS}	±20	
Continuous Drain Current [a]	T_A=25°C	I_D	21	A
	T_A=70°C		17.2	
Pulsed Drain Current [b]		I_{DM}	80	
Continuous Source Current (Diode Conduction) [a]		I_S	4.7	A
Power Dissipation [a]	T_A=25°C	P_D	3.5	W
	T_A=70°C		2	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	-55 to 150	°C

THERMAL RESISTANCE RATINGS				
Parameter		**Symbol**	**Maximum**	**Units**
Maximum Junction-to-Ambient [a]	t <= 10 sec	$R_{\theta JA}$	35	°C/W
	Steady State		81	

Notes

a. Surface Mounted on 1” x 1” FR4 Board.

b. Pulse width limited by maximum junction temperature

Electrical Characteristics

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Static						
Gate-Source Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 250 uA	1			V
Gate-Body Leakage	I_{GSS}	V_{DS} = 0 V, V_{GS} = ±20 V			±100	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 24 V, V_{GS} = 0 V			1	uA
		V_{DS} = 24 V, V_{GS} = 0 V, T_J = 55°C			25	
On-State Drain Current [a]	$I_{D(on)}$	V_{DS} = 5 V, V_{GS} = 10 V	30			A
Drain-Source On-Resistance [a]	$r_{DS(on)}$	V_{GS} = 10 V, I_D = 18.2 A			5.5	mΩ
		V_{GS} = 4.5 V, I_D = 14.6 A			7.8	
Forward Transconductance [a]	g_{fs}	V_{DS} = 15 V, I_D = 18.2 A		20		S
Diode Forward Voltage [a]	V_{SD}	I_S = 2.3 A, V_{GS} = 0 V		0.81		V
Dynamic [b]						
Total Gate Charge	Q_g	V_{DS} = 15 V, V_{GS} = 4.5 V, I_D = 18.2 A		19		nC
Gate-Source Charge	Q_{gs}			9.8		
Gate-Drain Charge	Q_{gd}			8.6		
Turn-On Delay Time	$t_{d(on)}$	V_{DS} = 15 V, R_L = 0.82 Ω, I_D = 18.2 A, V_{GEN} = 10 V, R_{GEN} = 6 Ω		12		ns
Rise Time	t_r			11		
Turn-Off Delay Time	$t_{d(off)}$			53		
Fall Time	t_f			16		
Input Capacitance	C_{iss}	V_{DS} = 15 V, V_{GS} = 0 V, f = 1 Mhz		2677		pF
Output Capacitance	C_{oss}			304		
Reverse Transfer Capacitance	C_{rss}			188		


Notes

a. Pulse test: PW <= 300us duty cycle <= 2%.


b. Guaranteed by design, not subject to production testing.

Analog Power (APL) reserves the right to make changes without further notice to any products herein. APL makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does APL assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. “Typical” parameters which may be provided in APL data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including “Typicals” must be validated for each customer application by customer’s technical experts. APL does not convey any license under its patent rights nor the rights of others. APL products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the APL product could create a situation where personal injury or death may occur. Should Buyer purchase or use APL products for any such unintended or unauthorized application, Buyer shall indemnify and hold APL and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that APL was negligent regarding the design or manufacture of the part. APL is an Equal Opportunity/Affirmative Action Employer.


Typical Electrical Characteristics




1. On-Resistance vs. Drain Current




2. Transfer Characteristics




3. On-Resistance vs. Gate-to-Source Voltage



4. Drain-to-Source Forward Voltage




5. Output Characteristics




6. Capacitance


Typical Electrical Characteristics




7. Gate Charge




8. Normalized On-Resistance Vs Junction Temperature



9. Safe Operating Area




10. Single Pulse Maximum Power Dissipation



11. Normalized Thermal Transient Junction to Ambient

Package Information



DIM.	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.700	0.80	0.900	0.0276	0.0315	0.0354
A1	0.00	---	0.05	0.000	---	0.002
b	0.24	0.30	0.35	0.009	0.012	0.014
c	0.10	0.152	0.25	0.004	0.006	0.010
D	3.00 BSC			0.118 BSC		
D1	2.35 BSC			0.093 BSC		
E	3.20 BSC			0.126 BSC		
E1	3.00 BSC			0.118 BSC		
E2	1.75 BSC			0.069 BSC		
E3	0.575 BSC			0.023 BSC		
e	0.65 BSC			0.026 BSC		
L	0.30	0.40	0.50	0.0118	0.0157	0.0197
L1	0	---	0.100	0	---	0.004
θ1	0°	10°	12°	0°	10°	12°